OnlylYou™ Face

An ATS Facial Recognition System





OnlyIYou[™] provides a more hygienic alternative to fingerprint readers or keypads, allowing for a safe, secure, and touchless work environment for your customers. OnlyIYou includes IDassist, a user-friendly User Interface that guides users during enrollment or daily use.

Benefits of Only You™

- Only You fully integrates with the stride®80.
- Only|You can deliver touchless workflows with your time collection application.
- Only|You intelligently adapts user templates through sustained use.
- Only You Delivers fast facial recognition results with low failure rate.
- Only|You delivers comprehensive SDK and API documentation for fast integration with your time collection application.
- Need to expedite your time-to-market?

- Only You increases workers' safety.
- Only You integrates with your existing badges or employee ID numbers.
- ATS provides on-going support and delivers secure remote software updates.
- The User Interface, IDassist, accurately guides users when enrolling or using the terminal during the identification process.

Bundle the stride80 with TimeCollect[™], and save months of development time and shorten your time-to-market. TimeCollect acts as an extension of your specific time clock functionality and branding.

Ask your account rep for details!

Only I You™ FRS	Licensed for use on ATS stride®80 terminals	ACCU-TIME SYSTEMS INC.
Operating System	Android OS 8.1 Oreo	Corporate Headquarters
User Interface	 8" Capacitive multi-touch color screen Software controllable multicolor LED indicator bar Microphone and speaker Presence sensor LED indicator for camera usage 8 Mega Pixel Camera Optional - Keypad 20 keys 0-9 F1-F6, Clear and Enter keys 	20-B International Drive Windsor, CT 06095 TEL: (860) 870-5000 FAX: (860) 872-1511 Toll Free: (800) 355-4648 sales@accu-time.com www.accu-time.com
Employee Template Capacity	Thousands of employee templates (Limited by the system memory and capacity)	EMEA & APAC United Kingdom
Mass Storage	16GB of which 5GB are user available	TEL: +44 (0) 1202 606068
Communications	10/100 Mpbs, Ethernet with DHCP, Static IP address Optional - 4G GSM Modem WIFI - 2.4Gbit/s, 802.11 b/g/n	All Other Locations TEL: +44 (0) 2920 885599
Dimensions	Base Model: 8.98" wide x 7.69" high x 3.13" deep 228.2mm wide x 195.3mm high x 79.6mm deep XL Model: 12.17" wide x 7.69" high x 3.13" deep 309.0mm wide x 195.3mm high x 79.6mm deep Mag swipe add on 1.16" x 3.74" x 1.34" 29.47mm x 96mm x 34.04mm	
Environment	Operating Temperature: 0° to 50°C (32° to 122°F)	
Memory	2GB	
Power	12 VDC 30W output Terminal power consumption less than 30 Watts Optional PoE IEEE 802.3at (30W, PoE+) Optional - Battery - Li-ion 8.4v @ 2600 mAh up to 1 hr of operation.	
Supported readers and card technologies	Optional Barcode scanner - Visible red light Optional Proximity readers - HID Prox, iClass SE, MiFare and Marin Optional Mag stripe reader - Track 1, 2, 3	
Relay	Up to 2 relays 48V/5A, Form C (AC/DC)	ATS