



Only|You™ Face

An ATS Facial Recognition System



Only|You™ provides a more hygienic alternative to fingerprint readers or keypads, allowing for a safe, secure, and touchless work environment for your customers. Only|You includes IDassist, a user-friendly User Interface that guides users during enrollment or daily use.

Benefits of Only|You™

- Only|You fully integrates with the stride®80.
- Only|You can deliver touchless workflows with your time collection application.
- Only|You intelligently adapts user templates through sustained use.
- Only|You Delivers fast facial recognition results with low failure rate.
- Only|You delivers comprehensive SDK and API documentation for fast integration with your time collection application.
- Only|You increases workers' safety.
- Only|You eliminates the complexities and costs associated with managing employee credentials.
- ATS provides on-going support and delivers secure remote software updates.
- The User Interface, IDassist, accurately guides users when enrolling or using the terminal during the identification process.

Need to expedite your time-to-market?

Bundle the stride80 with **TimeCollect™**, and save months of development time and shorten your time-to-market. TimeCollect acts as an extension of your specific time clock functionality and branding.

Ask your account rep for details!

OnlyYou™ FRS	Licensed for use on ATS stride®80 terminals
Operating System	Android OS 8.1 Oreo
User Interface	<p>8" Capacitive multi-touch color screen Software controllable multicolor LED indicator bar Microphone and speaker Presence sensor LED indicator for camera usage 8 Mega Pixel Camera</p> <p>Optional - Keypad</p> <ul style="list-style-type: none"> • 20 keys 0-9 • F1-F6, • Clear and Enter keys
Employee Template Capacity	Thousands of employee templates (Limited by the system memory and capacity)
Mass Storage	16GB of which 5GB are user available
Communications	<p>10/100 Mbps, Ethernet with DHCP, Static IP address</p> <p>Optional - 4G GSM Modem WIFI - 2.4Gbit/s, 802.11 b/g/n</p>
Dimensions	<p>Base Model: 8.98" wide x 7.69" high x 3.13" deep 228.2mm wide x 195.3mm high x 79.6mm deep</p> <p>XL Model: 12.17" wide x 7.69" high x 3.13" deep 309.0mm wide x 195.3mm high x 79.6mm deep</p> <p>Mag swipe add on 1.16" x 3.74" x 1.34" 29.47mm x 96mm x 34.04mm</p>
Environment	<p>Operating Temperature: 0° to 50°C (32° to 122°F) Operating Temperature with Battery: 0 to 34°C (32° to 93.2°F)</p>
Memory	2GB
Power	<p>12 VDC 30W output Terminal power consumption less than 30 Watts Optional PoE IEEE 802.3at (30W, PoE+) Optional - Battery - Li-ion 7.4v @ 2550 mAh up to 1 hr of operation.</p>
Supported readers and card technologies	<p>Optional - Barcode scanner - Visible red light Optional - Proximity readers - HID Prox, iClass SE, MiFare and Marin Optional - Mag stripe reader - Track 1, 2, 3</p>
Relay	Up to 2 relays 48V/5A, Form C (AC/DC)

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters
20-B International Drive
Windsor, CT 06095
TEL: (860) 870-5000
FAX: (860) 872-1511
Toll Free: (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

