



Prodigy™ - Affordable Time Keeping System

The Prodigy™ time clock has the ideal blend of performance, functionality, style, and affordability designed for essential workforce management functionality.

Prodigy is built for customers who demand a rich suite of features at an affordable price: Web services, customizable function keys, optional biometrics, and more!

Biometric options protect employees' personal information and eliminate costly buddy-punching.

Prodigy's™ features include:

- Internet appliance
- On-board diagnostics
- Biometric options for increased personal security
- Programmable function keys
- Ergonomic design with angled card slot
- Works in WAN and LAN environments
- Optional power-over-Ethernet module

To learn more about ATS and Prodigy, visit www.accu-time.com or call -1 860.870.5000



Prodigy Terminal Specifications

Display	<ul style="list-style-type: none">• 128 x 32 pixel LCD
Clock	<ul style="list-style-type: none">• Battery-backed real-time clock, 12- or 24-hour format (quartz precision)
Keypad	<ul style="list-style-type: none">• 16-key tactile 4x4 matrix<ul style="list-style-type: none">» Numeric keypad, 0-9» 4 software-defined function keys (e.g. in/out and two other functions)• Customizable overlay allows for unique graphic options
Memory	<ul style="list-style-type: none">• Linux: 32 MB RAM and 32 MB flash• Optional: Java™/Python 128 MB RAM and 128 MB flash
Programming	<ul style="list-style-type: none">• Java™ and Python options• Web services capable• ATS Universal Command Set or third-party custom application packages
Platform OS	<ul style="list-style-type: none">• Linux®
Diagnostics	<ul style="list-style-type: none">• On-Board Diagnostics Capability
Communication	<ul style="list-style-type: none">• Standard 802.3 10/100 BASE-T Ethernet with DHCP• Optional EIA standard RS232• Optional internal modem (FCC Part 68 certified)• USB port for mass storage device
Enclosure	<ul style="list-style-type: none">• High Impact Polymer
Power	<ul style="list-style-type: none">• 12 Vdc (Nominal) 1.25A, 15W Maximum• Optional Uninterruptible Power Supply With Charger• Optional IEEE 802.3af-compliant power over Ethernet
Environment	<ul style="list-style-type: none">• Operation Temperature: 0° To 50°C (32° To +122°F)• Storage Temperature: -20° To 80°C (-4° To +176°F)
Dimensions	<ul style="list-style-type: none">• 18.4 cm X 21.3 cm X 9.65 cm (7.25" X 8.40" X 3.80")•
Certifications	<ul style="list-style-type: none">• CE Mark, FCC Part 15 Class A
Accessories	<ul style="list-style-type: none">• Biometric readers – 1:1 and 1:n – fingerscan• Integrated visible or infrared barcode readers• Integrated magnetic stripe readers• Smartcard readers – contactless (HID® Prox, Mifare™, iClass®)• Integrated proximity readers• Solid-state or dry-contact relay modules• Serial interface for printer

ACCU-TIME SYSTEMS INC. THE AMERICAS

Corporate Headquarters
20-B International Drive
Windsor, CT 06095
TEL: (860) 870-5000
FAX: (860) 872-1511
Toll Free: (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

