



## The PeoplePoint™ Plus The Ultimate Time Tracking Device

The PeoplePoint Plus is a feature-packed time tracking device with a sleek 7" display, and a powerful processor. Its biometric technology improves accuracy, while the spacious screen facilitates easy navigation and effective content delivery to your valuable workforce. The PeoplePoint Plus ensures that employee data is seamlessly collected and sent to the back-end system for streamlined operations.

With its compatibility with multiple identification technologies and seamless data collection capabilities, it provides a comprehensive solution for efficient workforce management.

### Standard features include:

- Linux based
- Freescale iMX6 1GHz Single core
- 7" Widescreen touch display
- eMMC – 8GB storage

To learn more about ATS and the Plus, visit [www.accu-time.com](http://www.accu-time.com) or call -1 860.870.5000

# PeoplePoint™ Plus Terminal Specifications

<b>User Interface</b>	7" TFT Capacitive Touch, 800 x 480 Resolution 20-key tactile, 4x5 matrix <ul style="list-style-type: none"><li>• Numeric keypad 0-9</li><li>• Eight software definable function keys</li><li>• Clear/Enter keys</li></ul> Customizable overlay allows for unique graphic options
<b>CPU</b>	Freescale iMX6 up to 1GHz (Single Core)
<b>Memory</b>	1GB DDR3 RAM 512MB NAND FLASH
<b>Mass storage</b>	Non-removable eMMC 8GB, of which 2.0GB are user available
<b>Programming</b>	Linux OS standard. Java™/Python Web services - HTML capable Software Development Kit (SDK)
<b>Application software</b>	ATS AccuCollect - Configurable punch workflow management including job transfers, attestations, and more.
<b>Communications</b>	Standard 10/100 BASE-T Ethernet Internal USB port Optional - Wi-Fi with WPA support Optional - internal 3G cellular modem
<b>Enclosure</b>	PC/ABS
<b>Power</b>	12 VDC (nominal) 1A, 12W maximum under normal operation Optional - uninterruptible power supply Optional - IEEE 802.3af/compliant POE
<b>Environment</b>	Operation Temperature: 0° to 50°C (32° to +122°F) Storage Temperature: -20° to 80°C (-4° to +176°F)
<b>Dimensions</b>	H 26.67cm x W 22.86cm x D 10.16cm (H 10.5" x W 9" x D 4")
<b>Certifications</b>	CE Mark, FCC Part 15 Class A
<b>Accessories</b>	Biometric readers – 1:1 and 1:n Integrated visible or infrared barcode readers Integrated magnetic stripe readers Contactless smartcard readers (HID® Prox, Mifare™, iClass®, Marin) External readers - Wiegand compatible Dry contact low voltage relay modules dual Form C Uninterruptible power supply

## ACCU-TIME SYSTEMS INC. THE AMERICAS

Corporate Headquarters  
20-B International Drive  
Windsor, CT 06095  
TEL: (860) 870-5000  
FAX: (860) 872-1511  
Toll Free: (800) 355-4648  
sales@accu-time.com  
www.accu-time.com

## EMEA & APAC

United Kingdom  
TEL: +44 (0) 1202 606068

## All Other Locations

TEL: +44 (0) 2920 885599

