



Elevate your workforce management with PeoplePoint™ Premium, a 10.1" touch screen timekeeping solution that seamlessly integrates with Workday Time Tracking and Oracle HCM Cloud Time and Labor systems.

The PeoplePoint Premium provides unmatched visibility, user-friendliness, and valuable insights. It offers an intuitive platform for employees to interact with their schedules, request time off, and access vital information.

## Standard features include:

- 10.1" Widescreen Touch Display
- Seamless integration with Workday Time Tracking or Oracle HCM Cloud Time and Labor
- Configurable hardware to meet your needs: Biometric readers, proximity badge readers, barcode readers, swipe card reader, or keypads
- Configurable time clock software to meet your business and data collection requirements
- Easy to install and use out-of-the-box
- High-Performance Processor

# PeoplePoint™ Premium Terminal Specifications

DISPLAY	10.1" TFT Capacitive Touch, 16:9 Aspect Ratio, 1280 x 800
PROCESSOR	Freescale i.MX6 - Quad Core up to 1GHz
MEMORY	2GB DDR3 RAM 512MB NAND FLASH
MASS STORAGE	Non-removable eMMC 16GB, of which 5.6GB are user available
CLOCK	Battery-backed real-time clock, 12- or 24-hour format (quartz precision)
KEYPAD	20-key tactile, 4x5 matrix <ul style="list-style-type: none"><li>• Numeric keypad 0-9</li><li>• Eight software definable function keys</li><li>• Clear/Enter keys</li></ul> Customizable overlay allows for unique graphic options
PROGRAMMING	<ul style="list-style-type: none"><li>• Linux with Java™ / Python, web services / HTML</li><li>• Android-based with Android Studio, web services HTML 5</li></ul>
APPLICATION SOFTWARE	ATS AccuCollect - Configurable punch workflow and back-end communication interface. (on Linux)
DIAGNOSTICS	On-board and remote diagnostics capability
INTERFACE	<ul style="list-style-type: none"><li>• Standard 10/100/1000 BASE-T Ethernet</li><li>• Optional internal 3G cellular modem</li><li>• Internal USB port</li><li>• Optional 4-port USB hub</li></ul>
ENCLOSURE	PC/ABS
POWER	<ul style="list-style-type: none"><li>• 12 VDC (nominal) 2A, 24W maximum</li><li>• Optional uninterruptible power supply</li><li>• Optional IEEE 802.3af/compliant POE module</li></ul>
ENVIRONMENT	<ul style="list-style-type: none"><li>• Operation Temperature: 0° to 50°C (32° to +122°F)</li><li>• Storage Temperature: -20° to 80°C (-4° to +176°F)</li></ul>
DIMENSIONS	<ul style="list-style-type: none"><li>• H 32.4cm x W 30.73cm x D 10.16cm (H 12.75" x W 12.1" x D 4")</li></ul>
CERTIFICATIONS	CE Mark, FCC Part 15 Class A
ACCESSORIES	<ul style="list-style-type: none"><li>• Biometric readers – 1:1 and 1:n</li><li>• Integrated visible or infrared barcode readers</li><li>• Integrated magnetic stripe readers</li><li>• Smartcard readers - contact less (HID® Prox, Mifare™, iClass®, Marin)</li><li>• Optional external reader - Wiegand compatible</li><li>• Dry-contact relay modules (Dual form C 48V/2A)</li></ul>

ACCU-TIME SYSTEMS INC.  
THE AMERICAS

**Corporate Headquarters**  
20- International Drive  
Windsor, CT 06095  
TEL: +1 (860) 870-5000  
FAX: +1 (860) 872-1511  
Toll Free: 1 (800) 355-4648  
sales@accu-time.com  
www.accu-time.com

EMEA & APAC  
**United Kingdom**  
TEL: + 44 (0) 1202 606068  
sales@accu-time.com

All Other Locations  
TEL: +44 (0) 2920 885599  
sales@accu-time.com

