



The ATS family of PeoplePoint time and attendance terminals does more than simply record employee comings and goings. They provide a dynamic way to engage employees, glean insights into your business, and identify new ways to streamline processes and cut costs.

PeoplePoint Premium offers a new level of interaction for employee self-service applications. Designed with data security in mind, the 10.1" widescreen touch display makes it easy to navigate schedules, view accruals and enforce attestation. The terminal can also deliver training videos, support video chats, and display other web-based content. These capabilities are delivered through PeoplePoint Premium's rich graphics, speakers, and camera.

PeoplePoint Premium™ Features Include:

- Time clock is easy to install. A plug-and-play approach.
- Self-monitoring – Over 70 alerts are available that can be sent to the ATS Support Team and your technical staff.
- Time clock software is configured to fit your business processes.
- Supports bar code, magnetic stripe, proximity and smart card readers using existing badges.
- Time clock supports more than 60 languages.
- Deliver employee self-service functionality – attestation, request time off, view employee accrual balances, show employee schedules and more.

PeoplePoint Premium™ Terminal Specifications

DISPLAY	10.1" TFT Capacitive Touch, 16:9 Aspect Ratio, 1280 x 800 Resolution
PROCESSOR	Freescale i.MX6 - Quad Core up to 1GHz
CLOCK	Battery-backed real-time clock, 12- or 24-hour format (quartz precision)
KEYPAD	<ul style="list-style-type: none">- 20-key tactile 4x5 matrix- Numeric keypad 0-9- Eight software-defined function keys- Keys, Clear/Enter keys- Customizable overlay with your brand on the terminal
MEMORY	2GB DDR3 RAM 512MB NAND FLASH
MASS STORAGE	Non-removable eMMC 16GB, of which 5.6GB are user available
PROGRAMMING	Linux with Java™/Python, web services / HTML Android-based with Android Studio, web services HTML 5.
APPLICATION SOFTWARE	ATS AccuCollect - Configurable punch workflows and back-end communication interface (on Linux)
PLATFORM OS	Linux® or Android-based
DIAGNOSTICS	On-board and remote diagnostics capability
INTERFACE	<ul style="list-style-type: none">- Standard 10/100/1000 BASE-T Ethernet- Optional internal 3G cellular modem- Internal USB port- Optional 4-port USB hub
ENCLOSURE	PC/ABS
POWER	<ul style="list-style-type: none">- 12 VDC (nominal) 2A, 24W maximum- Optional uninterruptible power supply- Optional IEEE 802.3/at-compliant POE module
ENVIRONMENT	Operation Temperature: 0° to 50°C (32° to +122°F)
DIMENSIONS	H 32.4cm x W 30.73cm x D 10.16cm (H 12.75" x W 12.1" x D 4")
CERTIFICATIONS	CE Mark, FCC Part 15 Class A
ACCESSORIES	<ul style="list-style-type: none">- Biometric readers – 1:1 and 1:n- Integrated visible or infrared barcode readers- Integrated magnetic stripe readers- Smartcard readers – contactless (HID® Prox, Mifare™, iClass®, Marin)- Optional external reader - Wiegand compatible- Dry-contact relay modules (Dual form C, 48V/2A)

ACCU-TIME SYSTEMS INC. THE AMERICAS

Corporate Headquarters
420 Somers Road
Ellington, CT 06029
TEL: 1 (860) 870-5000
FAX: 1 (860) 872-1511
Toll Free: 1 (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: + 44 (0) 1202 606068
sales@accu-time.com

All Other Locations

TEL: +44 (0) 2920 885599
sales@accu-time.com

