## **PeoplePoint™ Plus**





## The PeoplePoint™ Plus time clock delivers the flexibility your customers' need

The PeoplePoint™ Plus employee time clock is the ideal time clock for those who require a comprehensive feature set, expandable memory, attractive design, and a color touch screen. With a Linux operating system, the PeoplePoint Plus delivers rich graphics and video on a 7″ widescreen display. Optional speakers and camera, a fast processor, and infinitely expandable memory will allow users to interact with detailed content. Developers are now able to deploy their WFM software in a manner designed for the people who use it.

Users can easily navigate employee self-service functionality on the generously sized screen. Custom programs, training videos, video chats, web browsers, and other custom content have a new, more effective platform now. The PeoplePoint Plus™ offers exciting gramming and content delivery opportunities.

To learn more about ATS and the Plus, visit <a href="https://www.accu-time.com">www.accu-time.com</a> or call -1 860.870.5000

## Standard features include:

- Linux based
- Freescale iMX6 1GHz Single core
- 7" Widescreen touch display
- Microphone
- eMMC 8GB storage





## **PeoplePoint™ Plus Terminal Specifications**

THE AMERICAS

Corporate Headquarters

20-B International Drive

ACCU-TIME SYSTEMS INC.

Windsor, CT 06095

TEL: (860) 870-5000

FAX: (860) 872-1511

Toll Free: (800) 355-4648 sales@accu-time.com

www.accu-time.com

**EMEA & APAC** 

United Kingdom

TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

7" TFT Capacitive Touch, 800 x 480 Resolution

20-key tactile, 4x5 matrix Numeric keypad 0-9

Eight software definable function keys

Clear/Enter keys

Customizable overlay allows for unique graphic options

Freescale iMX6 up to 1GHz (Single Core)

1GB DDR3 RAM 512MB NAND FLASH

Mass storage Non-removable eMMC

8GB, of which 2.0GB are user available

**Programming** Linux OS standard.

**User Interface** 

**CPU** 

Memory

Java™/Python

Web services - HTML capable Software Development Kit (SDK)

Application software • ATS AccuCollect - Configurable punch workflow management

including job transfers, attestations, and more.

**Communications** Standard 10/100 BASE-T Ethernet

Internal USB port

Optional Wi-Fi with WPA support

Optional internal 3G cellular modem

PC/ABS **Enclosure** 

12 VDC (nominal) 1A, 12W maximum under normal operation Power

Optional uninterruptible power supply

Optional IEEE 802.3af/compliant POE

Environment Operation Temperature: 0° to 50°C (32° to +122°F)

Storage Temperature: -20° to 80°C (-4° to +176°F)

**Dimensions** H 26.67cm x W 22.86cm x D 10.16cm (H 10.5" x W 9" x D 4")

Certifications CE Mark. FCC Part 15 Class A

**Accessories** Biometric readers – 1:1 and 1:n

Integrated visible or infrared barcode readers

Integrated magnetic stripe readers

Contactless smartcard readers (HID® Prox. Mifare™, iClass®, Marin)

External readers - Wiegand compatible

Dry contact low voltage relay modules dual Form C

Uninterruptible power supply

