

OnlyYou™ Palm

An ATS Palm Vein Reader System (PVR)



®

stride 80 with Palm Vein Reader

The stride80 equipped with a Palm Vein Reader module, makes it ATS's fastest, safest and most secure biometric solution for your customers' timekeeping needs.

The palm vein reader uses near-infrared rays to capture precise details of the veins in a person's palm and is converted into a biometric template that can be compared against a database of previously created and authorized templates to verify a person's identity.

Benefits of Using OnlyYou™ Palm

- OnlyYou Palm seamlessly integrates with stride80
- OnlyYou Palm easily integrates with HCM / WFM application
- OnlyYou Palm delivers touchless biometric technology
- OnlyYou Palm is the fastest solution for timekeeping needs
- OnlyYou Palm is the safest and most secure biometric solution
- OnlyYou Palm is highly accurate in identifying individuals
- OnlyYou Palm reduces time theft and buddy punching
- OnlyYou Palm is easy to mount and install
- OnlyYou Palm helps deliver a more accurate payroll

Need to expedite your time-to-market?

Bundle the stride80 with **TimeCollect™**, and save months of development time and shorten your time-to-market. TimeCollect acts as an extension of your specific time clock functionality and branding.

Ask your account rep for details!



Operating System	Android OS 8.1 Oreo
User Interface	8" Capacitive multi-touch color screen Software controllable multicolor LED indicator bar Microphone and speaker Presence sensor Optional - Keypad <ul style="list-style-type: none"> • 20 keys 0-9 • F1-F6, • Clear and Enter keys
Employee Template Capacity	Thousands of employee templates (Limited by the system memory and capacity)
Mass Storage	16GB of which 5GB are user available
Communications	10/100 Mbps, Ethernet with DHCP, Static IP address Optional - 4G GSM Modem WIFI - 2.4Gbit/s, 802.11 b/g/n
Dimensions	Palm Vein Reader Module: 3.125' wide x 2.625' high x 1.863 deep Base Model: 8.98" wide x 7.69" high x 3.13" deep 228.2mm wide x 195.3mm high x 79.6mm deep XL Model: 12.17" wide x 7.69" high x 3.13" deep 309.0mm wide x 195.3mm high x 79.6mm deep Mag swipe add on 1.16" x 3.74" x 1.34" 29.47mm x 96mm x 34.04mm
Environment	Operating Temperature: 0° to 50°C (32° to 122°F) Operating Temperature with Battery: 0 to 34°C (32° to 93.2°F)
Memory	2GB
Power	12 VDC 30W output Terminal power consumption less than 30 Watts Optional PoE IEEE 802.3at (30W, PoE+) Optional - Battery - Li-ion 7.4v @ 2550 mAh up to 1 hr of operation.
Supported readers and card technologies	Optional Barcode scanner - Visible red light Optional Proximity readers - HID Prox, iClass SE, MiFare and Marin Optional Mag stripe reader - Track 1, 2, 3
Relay	Up to 2 relays 48V/5A, Form C (AC/DC)

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters
20-B International Drive
Windsor, CT 06095
TEL: (860) 870-5000
FAX: (860) 872-1511
Toll Free: (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: +44 (0) 2920 885599

All Other Locations

TEL: +44 (0) 2920 885599

