



Efficiency Perfected stride®40 - The Future of Time and Attendance

The Stride40 is the ultimate time and attendance solution for small and mid-sized companies. This sleek device revolutionizes workforce management with its advanced biometric facial recognition system, touchscreen interface, and multiple clock-in methods.

Choose from HID Prox badges, Bar code scanner, or facial recognition (for up to 50 employees). With seamless integration and data security features, the Stride40 streamlines payroll operations and boosts productivity. Scale effortlessly, access data remotely, and invest in a more organized and productive workforce today.

stride®40 features include:

- Android-based
- 4" Touch Display
- Speaker
- Microphone
- eMMC – 16GB Storage

To learn more about ATS and stride40,
visit www.accu-time.com or
call -1 860.870.5000

stride®40 Terminal Specifications

Operating System	<ul style="list-style-type: none">• Android 8.1• Software Development Kit available
User Interface	<ul style="list-style-type: none">• 4" Capacitive multi-touch color screen• Speaker• Presence sensor - Maximum distance: 1500mm• LED indicator for camera usage• <u>Optional</u> - 8 Mega Pixel Camera - Supports photo and video• <u>Optional</u> - Custom logo inset
Memory	<ul style="list-style-type: none">• 2GB
Mass Storage	<ul style="list-style-type: none">• 16GB of which 10GB are user available
Central Processing Unit (CPU)	<ul style="list-style-type: none">• Quad Core A7, 1.1GHz
Communications	<ul style="list-style-type: none">• 10/100 BaseT Ethernet with DHCP, Static IP address• <u>Optional</u> - 4G GSM Modem<ul style="list-style-type: none">• LTE Europe B1/ B3/ B5/ B7/ B8/ B20; 850/ 900/ 1800/ 1900MHz• LTE US B2/ B4/ B5/ B7/ B12/ B13/ B25/ B26; 850/1900MHz• Wi-Fi - 2.4Gbit/s, 802.11 b/g/n• Bluetooth - BT 2.1 + EDR/3.0/4.1 LE (by default disabled)• USB - USB 2.0 Connectors Up to 480 Mbps
Dimensions	<ul style="list-style-type: none">• 8.198" wide x 7.73" high x 3.13" deep• 298.03mm wide x 196.34mm high x 79.50mm deep
Power	<ul style="list-style-type: none">• 12V DC 30W output Terminal power consumption less than 30 Watts• <u>Optional</u> - PoE IEEE 802.3at (30W, PoE+)• <u>Optional</u> - Battery - Li-ion 8.4v @ 2600 mAh up to 1 hr of operation.
Environment	<ul style="list-style-type: none">• Operating Temperature: 0° to 50°C (32° to 122°F)• Operating Temperature with Battery: 0 to 34°C (32° to 93.2°F)
Supported readers and card technologies	<ul style="list-style-type: none">• <u>Optional</u> - Optical Facial Recognition - Up to 50 enrollments• <u>Optional</u> - Barcode scanner - Visible red light• <u>Optional</u> - Proximity readers - HID Prox, MiFare

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters
20-B International Drive
Windsor, CT 06095
TEL: (860) 870-5000
FAX: (860) 872-1511
Toll Free: (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599